



TCM torbocar AC37

The small torbo unit - Versatile and specific!



Flexibly and independently thanks to water tank, hose-reel and compressor.

With 3,8 m³/mins or with 5,0 m³/mins (arming), you have enough compressed air for monument-care, facade-cleaning and easy renovation-works.

With a vessel-volume of 120 litres, you work up to 2 hours per filling.

With the **torbo**-System, you reduce your overheads and save the environment!

Volumen of vessel	l or dm ³ (Cu. ft.)	120 (4,24)
Air connection	mm (Zoll)	38 (1 1/2)
Compressor-connection (installed performance) - torbocar AC37 - torbocar AC37 with arming	m ³ /min (Cu. ft. per min)	3,8 (134) at 8 bar 5,0 (177) at 8 bar
Compressor-connection (min - max.)	m ³ /min (Cu. ft. per min) bar (PSI)	2,0 - 10,0 (70 - 350) 4,0 - 10,0 (57 - 142)
Pressurized water connection	bar (PSI)	up to 12 (up to 170)
Stream-connection (installed)	V (W)	12 (1,2)
Connection blasting hose	mm (Zoll)	38 (1 1/2)
Consumption of blasting media (min - max)	l/h (Cu. ft. per h)	14,5 - 288 (0,5 - 10,2)
Dimensions, approx. (H x W x L)	mm Zoll	1.850 x 1.880 x 5.450 72 ,3 x 74 x 214,6
Weight (empty)	kg (lbs.)	1.370 (3.014)
Permissible total weight (max.)	kg (lbs.)	1.500 to 2.000 (3.3.00 to 4.400)

Telefon: +66 76 278038
 Telefax: +66 76 279088
 Email: office@tcm-asia.com
www.tcm-asia.com

TCM Asia Co., Ltd
 78/23 Moo3 Kamala Kathu
 83120 Phuket
 Thailand